

---

## 1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND COMPANY/ UNDERTAKING

<b>Material Name</b>	: <b>Methyl Ethyl Ketone</b>
<b>Product Code</b>	: S2113
<b>Supplier</b>	: Chemisol Inc. 3/F Johnson Bldg. #5 D. Muñoz St. Tandang Sora, Quezon City Philippines
<b>Telephone</b>	: (632) 938 5388
<b>Fax</b>	: (632) 938 3818
<b>Emergency Telephone Number</b>	: (632) 938 5388
<b>Recommended use of the chemical and restrictions on use</b>	
<b>Recommended use</b>	: Use only in industrial processes.
<b>Restrictions on use</b>	: This product must not be used in applications other than the above without first seeking the advice of the supplier.

---

## 2. HAZARDS IDENTIFICATION

<b>GHS Classification</b>	: Flammable liquids, Category 2 Acute toxicity (Oral), Category 5 Aspiration hazard, Category 2 Eye irritation, Category 2A Specific target organ toxicity - single exposure, Category 3 (Narcotic effects)
---------------------------	---

<b>GHS Label Statements</b>	
<b>Symbol</b>	:



<b>Signal Words</b>	: Danger
<b>GHS Hazards Statements</b>	: <b>PHYSICAL HAZARDS:</b> H225 Highly flammable liquid and vapour.  : <b>HEALTH HAZARDS:</b> H303 May be harmful if swallowed. H305 May be harmful if swallowed and enters airways. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.  : <b>ENVIRONMENTAL HAZARDS:</b> Not classified as an environmental hazard under GHS criteria.

## Safety Data Sheet

**GHS Precautionary statements****Prevention**

: P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash hands thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response**

: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P370 + P378 In case of fire: Use appropriate media to extinguish.  
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P331 Do NOT induce vomiting.

**Storage**

: P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P235 Keep cool.  
 P405 Store locked up.

**Disposal**

: P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

**Other Hazards which do not result in classification**

: Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Exposure may enhance the toxicity of other materials. See Chapter 11 for details. Repeated exposure may cause skin dryness or cracking.

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**

Substance/Mixture : Substance

**Hazardous components**

Chemical Name	CAS-No. EC-No. Registration number	Classification	Concentration
Methyl ethyl ketone	78-93-3	Flam.Liq. 2; H225 Acute Tox. 5; H303 Asp. Tox. 2; H305 Eye Irrit. 2; H319 STOT SE3; H336	100

---

**4. FIRST AID MEASURES**

<b>General advice</b>	: DO NOT DELAY Keep victim calm. Obtain medical treatment immediately.
<b>If inhaled</b>	: Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
<b>In case of skin contact</b>	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
<b>In case of eye contact</b>	: Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.
<b>If swallowed</b>	: If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.
<b>Most important symptoms and effects, both acute and delayed</b>	: If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.
<b>Protection of first-aiders</b>	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
<b>Notes to physician</b>	: Potential for chemical pneumonitis. Consider: gastric lavage with protected airway, administration of activated charcoal. Call a doctor or poison control center for guidance.

---

**5. FIRE FIGHTING MEASURES**

<b>Suitable extinguishing Media</b>	: Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing Media</b>	: None

## Safety Data Sheet

**Specific hazards during Firefighting**

: The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Carbon monoxide may be evolved if incomplete combustion occurs.

**Specific extinguishing methods**

: Standard procedure for chemical fires.  
Clear fire area of all non-emergency personnel.  
Keep adjacent containers cool by spraying with water.

**Special protective Equipment for firefighters**

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

---

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, Protective equipment and emergency procedures**

: Observe the relevant local and international regulations  
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.  
Local authorities should be advised if significant spillages cannot be contained.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Vapour may form an explosive mixture with air.  
Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Stay upwind and keep out of low areas.

**Environmental Precautions**

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.  
Ventilate contaminated area thoroughly.  
Monitor area with combustible gas indicator.

**Methods and materials for containment and cleaning up**

: For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely  
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up

with an appropriate absorbent material and dispose of safely Remove contaminated soil and dispose of safely.

**Additional advice** : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.  
For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

---

## 7. HANDLING STORAGE

**General Precautions** : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  
Ensure that all local regulations regarding handling and storage facilities are followed.

**Advice on safe handling** : Avoid contact with skin, eyes and clothing.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

**Avoidance of contact** : Strong oxidising agents.

**Advice on protection  
Against fire and explosion** : Bulk storage tanks should be diked (bunded). Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Do NOT use compressed air for filling, discharging, or handling operations.

**Product Transfer** : Refer to guidance under Handling section.

**Storage  
Conditions for safe  
storage** : The vapour is heavier than air. Beware of accumulation in pits and confined spaces.  
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

**Packaging material** : Suitable material: For containers, or container linings use mild steel, stainless steel.

**Unsuitable material** : Natural, butyl, neoprene or nitrile rubbers

**Container Advice** : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

**Specific use(s)** : Not applicable

Ensure that all local regulations regarding handling and storage facilities are followed.

See additional references that provide safe handling practices:

American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).

CENELEC CLC/TR 50404 (Electrostatics – Code of practice for the avoidance of hazards due to static electricity).

## 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible Concentration	Basis
Methyl ethyl ketone	78-93-3	PEL (short term)	300 ppm 885 mg/m <sup>3</sup>	SG OEL
		PEL (long term)	200 ppm 590 mg/m <sup>3</sup>	SG OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m <sup>3</sup>	OSHA Z-1

### Biological occupational exposure limits

No biological limit allocated.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier.

Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods

<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods

<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances

<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany

<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

## Safety Data Sheet

Firewater monitors and deluge systems are recommended.  
Eye washes and showers for emergency use.  
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

**General Information**

: Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

**Personal protective equipment****Protective measures**

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

**Respiratory protection**

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

Check with respiratory protective equipment suppliers.

Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use:

Select a filter suitable for organic gases and vapours [boiling point >65 °C (149 °F)].

**Hand protection****Remarks**

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Butyl rubber. Nitrile rubber. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove

## Safety Data Sheet

material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

<b>Eye protection</b>	: Wear goggles for use against liquids and gas. Wear full face shield if splashes are likely to occur.
<b>Skin and body Protection</b>	: Wear antistatic and flame retardant clothing if a local risk assessment deems it so. Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.
<b>Thermal hazards</b>	: Not applicable
<b>Hygiene measures</b>	: Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use.
<b>Environmental exposure</b>	
<b>Controls General advice</b>	: Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in section 6.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	: Liquid.
<b>Colour</b>	: clear
<b>Odour</b>	: characteristic
<b>Odour Threshold</b>	: Data not available
<b>pH</b>	: Not applicable
<b>Melting / freezing point</b>	: -86°C / -123°F
<b>Boiling point/boiling range</b>	: 79.5°C / 175.1°F
<b>Flash point</b>	: -9°C / 16°F
<b>Upper explosion limit</b>	: upper flammability limit 11.5% (V)
<b>Lower explosion limit</b>	: lower flammability limit 1.8% (V)
<b>Vapour pressure</b>	: 12.600 Pa (20°C / 68°F)
<b>Relative vapour density</b>	: 2.4 (20°C / 68°F)
<b>Relative density</b>	: 804-806 (20°C / 68°F) Method: ASTM D4052
<b>Density</b>	: 804-806 kg/m <sup>3</sup> (20°C / 68°F) Method: ASTM D4052



## Safety Data Sheet

<b>Solubility (ies)</b>	
<b>Water solubility</b>	: 250 g/l Miscible. (20°C / 68°F)
<b>Partition coefficient</b>	:
<b>n-octanol/water</b>	: log Pow: 0.3
<b>Auto-ignition temperature</b>	: 515°C / 959°F
<b>Decomposition Temperature</b>	: no data available
<b>Viscosity, dynamic</b>	: 0.42 mPa.s (20°C / 68°F)
<b>Viscosity, kinematic</b>	: Data not available
<b>Explosive properties</b>	: Not applicable
<b>Oxidizing properties</b>	: Data not available
<b>Conductivity</b>	: Electrical conductivity: > 10 000 pS/m, A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid, This material is not expected to be a static accumulator.
<b>Molecular weight</b>	: 72.11 g/mol

---

**10. STABILITY AND REACTIVITY**

<b>Reactivity</b>	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
<b>Chemical stability</b>	: No hazardous reaction is expected when handled and stored according to provisions
<b>Possibility of hazardous Reactions</b>	: Reacts with strong oxidising agents.
<b>Conditions to avoid</b>	: Avoid heat, sparks, open flames and other ignition sources. Prevent vapour accumulation. In certain circumstances product can ignite due to static electricity.
<b>Incompatible materials</b>	: Strong oxidising agents.
<b>Hazardous decomposition Products</b>	: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

---

**11. TOXICOLOGICAL INFORMATION**

<b>Basis for assessment</b>	: Information given is based on product testing.
-----------------------------	--

## Safety Data Sheet

**Information on likely routes of Exposure**

: Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

**Acute toxicity****Product****Acute oral toxicity**: LD50 Rat: >2000 - <= 5000 mg/kg  
Remarks: May be harmful if swallowed.**Acute inhalation toxicity**: LC50 : 5000 ppm  
Remarks: Low toxicity:**Acute dermal toxicity**: LD50 Rabbit: > 5,000 mg/kg  
Remarks: Low toxicity:**Skin corrosion/irritation Product**

: Remarks: Not irritating to skin.

**Serious eye damage/ eye irritation****Product**

: Remarks: Causes serious eye irritation.

**Respiratory or skin sensitization****Product**

: Remarks: Not expected to be a sensitiser.

**Germ cell mutagenicity****Product**

: Remarks: Not mutagenic.

**Carcinogenicity****Product**

: Remarks: Not expected to be carcinogenic.

Material	GHS/CLP Carcinogenicity Classification
Methyl ethyl ketone	No carcinogenicity classification

**Reproductive toxicity****Product**

: Remarks: Not expected to impair fertility., Not a developmental toxicant.

**STOT - single exposure****Product**

: Remarks: May cause drowsiness and dizziness.

**STOT - repeated exposure****Product**

: Remarks: Low systemic toxicity on repeated exposure., Repeated exposure may cause skin dryness or cracking.

**Aspiration toxicity****Product**

: Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Safety Data Sheet

**Further information  
Product**

: Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

---

**12. ECOLOGICAL INFORMATION**

**Basis for assessment**

: Information given is based on product testing.

**Ecotoxicity**

**Product :**

**Toxicity to fish**

**(Acute toxicity)**

: Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

**Toxicity to crustacean**

**(Acute toxicity)**

: Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

**Toxicity to algae/  
aquatic plants**

**(Acute toxicity)**

: Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

**Toxicity to fish**

**(Chronic toxicity)**

: Remarks: Data not available

**Toxicity to crustacean**

**(Chronic toxicity)**

: Remarks: Data not available

**Toxicity to microorganisms**

**(Acute toxicity)**

: Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

**Persistence and degradability**

**Product**

:

**Biodegradability**

: Remarks: Readily biodegradable., Oxidises rapidly by photo-chemical reactions in air.

**Bioaccumulative potential**

**Product**

:

**Bioaccumulation**

: Remarks: Not expected to bioaccumulate significantly.

**Partition coefficient**

:

**n-octanol/water**

: log Pow: 0.3

**Mobility in soil**

**Product**

:

**Mobility**

: Remarks: Dissolves in water.

**Other adverse effects**

: no data available

**Product**

:

**Additional ecological  
Information**

: Not expected to have ozone depletion potential.

---

**13. DISPOSAL CONSIDERATIONS****Material Disposal**

: Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses

Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

**Container Disposal**

: Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard.

Do not, puncture, cut, or weld uncleaned drums.

Send to drum recoverer or metal reclaimer.

---

**14. TRANSPORT CONSIDERATIONS****International Regulation****ADR**

UN number : 1193  
Proper shipping name : ETHYL METHYL KETONE, (METHYL ETHYL KETONE)  
Class : 3  
Packing group : II  
Labels : 3  
Hazard Identification Number :33  
Environmentally hazardous : no

**IATA-DGR**

UN/ID No. : UN 1193  
Proper shipping name : METHYL ETHYL KETONE  
Class : 3  
Packing group : II  
Labels : 3

**IMDG-Code**

UN number : UN 1193  
Proper shipping name : ETHYL METHYL KETONE, (METHYL ETHYL KETONE)  
Class : 3  
Packing group : II  
Labels : 3  
Marine pollutant : no

## Safety Data Sheet

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

**Pollution category** : Z  
**Ship type** : 3  
**Product name** : Methyl ethyl ketone

**Special precautions for user**

**Remarks** : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

**Additional Information**

: This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

---

**15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product Classification, Labelling and SDS: DOLE Administrative Order 136-14 Guidelines for the Implementation of GHS in Chemical Safety Program in the Workplace.

Other international regulations

The components of this product are reported in the following inventories:

**AICS** : Listed  
**DSL** : Listed  
**IECSC** : Listed  
**KECI** : Listed  
**PICCS** : Listed  
**EINECS** : Listed  
**TSCA** : Listed

---

**16. OTHER INFORMATION****Full text of H-Statements**

H225 Highly flammable liquid and vapour.  
H303 May be harmful if swallowed.  
H305 May be harmful if swallowed and enters airways.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**Full text of other abbreviations**

Acute Toxicity	Acute toxicity
Asp. Tox.	Aspiration hazard
Flam. Liq.	Flammable liquids
Eye Irrit	Eye irritation
STOT SE	Specific target organ toxicity - single exposure

Safety Data Sheet

**Abbreviations and Acronyms** : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

**Further information**  
**Training advice** : Provide adequate information, instruction and training for operators.

**Sources of key data used to compile the Safety Data Sheet** : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.